



Performance Pump & Equipment

Performance Pump & Equipment Company Limited
Unit 12, Tattenham Works, Hindley Green, Wigan WN2 4SZ

enquiries@performancepump.co.uk
www.performancepumps.co.uk

Tel: 01942 259621
Fax: 01942 258549

Inflatable Pipe Stoppers

Performance Pump & Equipment are leading suppliers of Inflatable Pipe and Sewer Stoppers for hire throughout the UK

Inflatable Pipe Stoppers (also referred to as Blank Stoppers, Bungs and Pipe Plugs) are designed to seal circular pipes and sewers and to stop flows; they can also be used as a rear seal when used in conjunction with test stoppers.

Inflatable By Pass Stoppers are used when it is not possible to completely stop the flow in the pipe or sewer and where a method of diverting the flow is required. The bypass stopper can be connected to hose and pumps so that flows can be maintained and diverted past sections of pipe or sewer requiring attention.

Inflatable Test Stoppers are used to seal off pipes and sewers so that air and water pressure tests can be completed.

Stoppers can be inflated with either hand operated pumps or compressor type controllers. Please advise which type you require.



Inflatable Stoppers

	Pipe Diameter	Deflated Bag Diameter	Operating Pressure	Cylinder Length Excluding Fittings	Weight Excluding Fittings
10/20	10-20 cm / 3.9-7.9 inch	9 cm / 3.5 inch	2.5 bar / 36.5 psi	51 cm / 20 inch	1.20 kg / 2.7 lbs
20/50	20-50 cm / 7.9-19.7 inch	19.5 cm / 7.7 inch	2.5 bar / 36.5 psi	75 cm / 29.5 inch	5 kg / 11 lbs
30/60	30-60 cm / 12-24 inch	29.5 cm / 11.6 inch	2.5 bar / 36.5 psi	73.5 cm / 28.9 inch	7 kg / 15.4 lbs
50/100	50-100 cm / 19.7-39.4 inch	45 cm / 17.7 inch	1.5 bar / 21.75 psi	111 cm / 43.7 inch	17 kg / 37.5 lbs
60/120	60-120 cm / 24-47.2 inch	58 cm / 22.8 inch	1.5 bar / 21.75 psi	132 cm / 52 inch	25 kg / 55 lbs
80/140	80-140 cm / 31.5-55.1 inch	78.5 cm / 30.9 inch	1.5 bar / 21.75 psi	181 cm / 71.3 inch	41 kg / 90.40 lbs
140/170	140-170 cm / 55.1-67 inch	135 cm / 53.2 inch	0.5 bar / 7.25 psi	190 cm / 74.8 inch	55 kg / 121.30 lbs
170/200	170-200 cm / 67-78.7 inch	162 cm / 63.8 inch	0.5 bar / 7.25 psi	190 cm / 74.8 inch	59 kg / 130.10 lbs

Bypass Stoppers

	Pipe Diameter	Deflated Bag Diameter	Operating Pressure	Cylinder Length Excluding Fittings	Weight Excluding Fittings
10/20	10-20 cm / 4-8 inch	9.7 cm / 3.9 inch	1.5 bar / 21.75 psi	48.5 cm / 19.1 inch	2.2 kg / 4.9 lbs
20/50	20-50 cm / 8-20 inch	19.5 cm / 7.7 inch	1.5 bar / 21.75 psi	55 cm / 21.7 inch	7 kg / 15.4 lbs
50/120	50-120 cm / 20-47 inch	45 cm / 17.7 inch	1.5 bar / 21.75 psi	92 cm / 36.2 inch	42.5 kg / 93.7 lbs

Test Stoppers

	Pipe Diameter	Deflated Bag Diameter	Operating Pressure	Cylinder Length Excluding Fittings	Weight Excluding Fittings
50/100	50-100 cm / 19.7-39.4 inch	45 cm / 17.7 inch	1.5 bar / 21.75 psi	111 cm / 43.7 inch	27-36kg / 59.5-79.4 lbs
80/140	80-140 cm / 31.5-55.1 inch	78.5 cm / 30.9 inch	1.5 bar / 21.75 psi	181 cm / 71.3 inch	55-69 kg / 121.3-152.2 lbs
140/170	140-170 cm / 55.1-67 inch	135 cm / 53.2 inch	0.5 bar / 7.25 psi	190 cm / 74.8 inch	62.5-70 kg / 137.8-154.4 lbs
170/200	170-200 cm / 67-78.7 inch	162 cm / 63.8 inch	0.5 bar / 7.25 psi	190 cm / 74.8 inch	64.5-70 kg / 142.2-154.4 lbs

Please Note: It is critical that all stoppers are used as per the manufacturer's recommendations, copies of which will be supplied with every item hired.

Hire Hotline: 0844 736 5964